

KAVSES O-RING CHAMFERING DIMENSIONS

CROSS-SECTION
b [mm]
1,50
1,78
2,00
2,40
2,50
2,62
3,00
3,53
4,00
4,50
5,00
5,34
5,70
6,00
6,50
7,00
7,50
8,00
8,50
9,00
9,50
10,00
11,00
12,50
15,00

STATIC	
B [mm]	T [mm]
1,90	1,10
2,30	1,30
2,60	1,50
3,10	1,80
3,20	1,90
3,40	2,00
3,90	2,30
4,50	2,75
5,20	3,15
5,80	3,60
6,50	4,00
6,90	4,30
7,40	4,65
7,80	4,95
8,40	5,40
9,10	5,85
9,70	6,30
10,40	6,75
11,00	7,25
11,70	7,70
12,30	8,20
13,00	8,65
14,30	9,65
16,20	11,05
19,50	13,50

DYNAMIC		
B [mm]	HYDRAULIC T [mm]	PNEUMATIC T [mm]
1,90	1,30	1,35
2,30	1,50	1,55
2,40	1,70	1,75
2,90	2,10	2,15
3,00	2,20	2,30
3,10	2,30	2,40
3,60	2,60	2,75
4,20	3,10	3,25
4,80	3,50	3,65
5,40	4,00	4,20
6,00	4,45	4,65
6,40	4,70	4,95
6,90	5,10	5,35
7,20	5,40	5,65
7,80	5,80	6,10
8,40	6,30	6,60
9,00	6,70	7,10
9,60	7,20	7,60
10,20	7,70	8,10
10,80	8,20	8,60
11,40	8,70	9,10
12,00	9,20	9,60
13,20	10,20	10,60
15,00	11,70	12,10
18,00	14,20	14,60

